

MATERIAL SAFETY
DATA SHEET

Product Name: Work Zone Painter's Acrylic Latex Caulk - White
Product Code: Series 039

Section I - Company Information

Company:	ICB Products 75 Chambers Drive, Unit 9 Ajax, Ontario, L1Z 1E1 Canada	Information Tel. No. (905) 619-0115 Emergency Tel. No. (905) 619-0115
----------	---	--

Date Prepared: January 1, 2015

Section II - Hazardous Chemical Ingredients/Identity Information

Ingredient	CAS#	% BY WGT	TLV/PPM	TLV/MG/CM	LEL	PEL	VAPOUR PRESSURE
Mineral spirits	64742-88-7	1	100	N/A	1.0	500	2mm HG @ 68°F

Section III – Hazards Identification

Emergency Overview:

Description: Material is an aqueous water based sealant, white in colour.
Presents little or no hazard if spilled or involved in a fire.

Potential Health Effects:

Eye:	May cause slight irritation.
Skin:	Prolonged exposure may cause slight irritation.
Ingestion:	Small amounts swallowed during normal handling are not likely to cause injury.

Section IV – First Aid Measures

Emergency & First Aid Procedures:

Ingestion:	Consult physician.
Eye Contact:	Flush eyes with water for at least 15 minutes and consult a physician.
Skin Contact:	Wash with soap and water.

Section V – Fire Fighting Measures

Flammable Properties:	Flammability Classification:
Not flammable as supplied.	OSHA = Combustible liquid – class III B
Flash point is greater than 200°F	DOT = Not regulated

Extinguishing Media:

Use National Fire Protection Association (NFPA) class B extinguishers (carbon dioxide, dry chemical, or foam) designed to extinguish NFPA class B liquid fires.

Fire Fighting Instructions:

Wear full protective equipment, eye/face shield, full body protection, SCBA respirator. Cool containers with water spray.

Section VI – Accidental Release Measures

Steps To Be Taken In Case Material Is Spilled:

Area may be slippery, care should be taken to prevent falls.
Keep spill out of sewers and open bodies of water.

Waste Disposal Methods:

Dispose of in accordance with local, provincial, and federal regulations.

Section VII – Handling And Storage

Handling:

Avoid contact with skins, eyes, or clothes.
Wash thoroughly after handling.

Storage:

Do not store above 140°F.
Keep from freezing.

Section VIII – Exposure Controls And Personal Protection

Engineering Controls:

No specific controls are needed.

Personal Protective Equipment:

Safety eye wear with side shields.

Exposure Guidelines:

Not established.

Section IX – Physical And Chemical Properties

Characteristics:

Appearance:	White paste	Viscosity:	20 – 24 GPS @ 77°F
Odour:	Light acrylic	Vapour Pressure:	Data not available
Ph:	7.5 – 7.9	Vapour Density:	Heavier than air
Solubility:	Water soluble	Specific Gravity:	1.70
Boiling Point:	Data not available	Freezing Point:	0°C (32°F)

Section X – Stability And Reactivity

Stability:

This material is stable.

Conditions To Avoid:

None.

Hazardous Polymerization:

This will not occur.

Incompatibility:

None.

Hazardous Decomposition Products:

At very high temperatures decomposition may evolve carbon monoxide, carbon dioxide and toxic monomer fumes.

Section XI - Regulatory Information

This product has been classified in accordance with the hazard criteria of the CFR and the MSDS contains all the information required by the CFR.

Section XII - Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.